



S600EM-W

Description

- Zinc alloy case, anti-vandal
- Waterproof, outdoor and indoor use
- 2000 users, support card, PIN, card + PIN
- Backlit keypad
- WG26 input and output
- Built-in buzzer alarm for anti-tamper
- With doorbell key, can connect with external doorbell
- Adjustable door open time and alarm time
- Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*56*20mm
Gross Weight	0.51KGS



S100EM

Description

- Zinc alloy case, anti-vandal
- Waterproof, outdoor and indoor use
- 2000 users, support card, PIN, card + PIN
- Backlit keypad
- WG26 input and output
- Built-in buzzer alarm for anti-tamper
- With doorbell key, can connect with external doorbell
- Adjustable door open time and alarm time
- Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*80*25mm
Gross Weight	0.75KGS



S500EM-W

Description

- Zinc alloy case, anti-vandal
- Waterproof, outdoor and indoor use
- 2000 users, support card, PIN, card + PIN
- Backlit keypad
- WG26 input and output
- Built-in buzzer alarm for anti-tamper
- With doorbell key, can connect with external doorbell
- Adjustable door open time and alarm time
- Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*80*25mm
Gross Weight	0.75KGS



K8EM-W

Description

Zinc alloy case, anti-vandal
Waterproof, outdoor and indoor use
2000 users, support card, PIN, card + PIN
Backlit keypad
WG26 input and output
Built-in buzzer alarm for anti-tamper
With doorbell key, can connect with external doorbell
Adjustable door open time and alarm time
Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	118*78*25mm
Gross Weight	0.70KGS



K9EM-W

Description

- Zinc alloy case, anti-vandal
- Waterproof, outdoor and indoor use
- 2000 users, support card, PIN, card + PIN
- Backlit keypad
- WG26 input and output
- Built-in buzzer alarm for anti-tamper
- With doorbell key, can connect with external doorbell
- Adjustable door open time and alarm time
- Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*80*25mm
Gross Weight	0.75KGS



N1EM

Description

- Zinc alloy case, anti-vandal
- Waterproof, outdoor and indoor use
- 2000 users, support card, PIN, card + PIN
- Backlit keypad
- WG26 input and output
- Built-in buzzer alarm for anti-tamper
- With doorbell key, can connect with external doorbell
- Adjustable door open time and alarm time
- Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	140*43*25mm
Gross Weight	0.70KGS



S601EM-W

Description

Zinc alloy case, anti-vandal, silica gel button/keys
 Waterproof, outdoor and indoor use
 2000 users, support card, PIN, card + PIN
 Backlit keypad
 WG26 input and output
 Built-in buzzer alarm for anti-tamper
 With doorbell key, can connect with external doorbell
 Adjustable door open time and alarm time
 Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*56*20mm
Gross Weight	0.50KGS



S602EM-W

Description

Aluminum alloy case, anti-vandal, silica gel button/keys

Waterproof, outdoor and indoor use

2000 users, support card, PIN, card + PIN

Backlit keypad

WG26 input and output

Built-in buzzer alarm for anti-tamper

With doorbell key, can connect with external doorbell

Adjustable door open time and alarm time

Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*56*20mm
Gross Weight	0.50KGS



S603EM-W

Description

Aluminum alloy case, anti-vandal, silica gel button/keys

Waterproof, outdoor and indoor use

2000 users, support card, PIN, card + PIN

Backlit keypad

WG26 input and output

Built-in buzzer alarm for anti-tamper

With doorbell key, can connect with external doorbell

Adjustable door open time and alarm time

Red, Yellow and Green LEDs display the working status

Specifications

Card Type	EM
Frequency	125KHz
Working Voltage	DC 12V
Reading range	5~8cm
Waterproof degree	IP68
Operating Humidity	10%~90%
Alarm output load	≤20A
Door opening time	0~99s (adjustable)
Idle Current	≤30mA
Operating Temperature	-35℃~60℃
Lock output load	≤3A
Short-circuit protection time	≤100 μs
Dimensions	120*56*20mm
Gross Weight	0.50KGS